

PRODUCT TECHNICAL DATA SHEET

FLEET GUARD PLUS SAE 15W40 API CI4

Super Heavy Duty Diesel Engine Oil

PRODUCT DESCRIPTION

FLEET GUARD PLUS SAE 15W40 API CI4 is a super high performance long drain diesel engine oil meeting the latest **API CI4** standard available in a shear stable viscosity grade. This lubricant has been developed as a long life oil meeting Mercedes Benz 228.3 and Volvo VDS-3 long oil drain specifications. **FLEET GUARD PLUS SAE 15W40 API CI4** offers the excellent performance for fleet operators wanting long engine life in modern long haul diesel trucks operating with low emission engine standards meeting Euro 4 and for extended drain periods. The product is manufactured with mineral base API approved base oils and imparted with chemical additives qualifying **API CI4/SL**.

APPLICATIONS

- ★ Mixed fleets of automotive diesel truck manufacturers
- ★ Modern low emission high performance automotive diesel engines - Euro 4
- ★ All vehicle makes used in long distance transport with extended oil drain capabilities
- ★ Heavy duty Mobile Plant vehicles
- ★ Diesel generator sets

PERFORMANCE STANDARDS

FLEET GUARD PLUS SAE 15W40 API CI4 meets and exceeds the following OEM and International specifications:

API	CI4/SL
ACEA	E5-02, E7-04
Mercedes Benz	228.3
Volvo	VDS-3
MACK	EO-N
MTU	Type 2
Renault	VI RLD/RLD-2
Cummins	20076/20077 and 20078
MAN	M 3275-1
Caterpillar	ECF 1 & ECF- 2

Always follow equipment manufacturer's recommendation for required lubricant performance levels and oil drain intervals.

DOCUMENT INFORMATION

Issued by	Qatar Fuel (WOQOD) – Lubricants Section	Doc. Ref. No.	WL/TDS/F001
Last Update	24.03.2016	Page No.	1 of 2

BENEFITS

FLEET GUARD PLUS SAE 15W40 API CI4 provides:

- ★ Excellent engine cleanliness through advanced soot handling technology
- ★ Mixed fleet capabilities
- ★ Exceptional low engine wear
- ★ Trouble free operation between long drain service intervals

TECHNICAL DATA*

SAE Grade	15W40	20W50
Kinematic Viscosity:		
mm ² /s @ 40 °C	106.2	190.1
mm ² /s @100 °C	14.75	21.29
Viscosity Index	144	132
Flash Point COC, °C	224	238
Pour Point, °C	-30	-27
BN No. ASTM D2896	11	11
Sulphated Ash % m	1.66	1.6

*The information prepared provides the typical properties that are considered as representative. Some variation which will not affect performance is possible.

HEALTH & SAFETY, ENVIRONMENT

The information on this product is available in the WOQOD Material Safety Data Sheet (MSDS) as a guide to the precautions and safe handling of this product and its disposal. For further information we recommend you review the MSDS. Handled correctly there are no special precautions suggested.

DOCUMENT INFORMATION

Issued by	Qatar Fuel (WOQOD) – Lubricants Section	Doc. Ref. No.	WL/TDS/F001
Last Update	24.03.2016	Page No.	2 of 2